





# TESA Setting Rinas and Setting Masters



Shiboina box

No identification number



			
	mm	µm*	µm**
<i>Setting rinas</i>			
<b>00843200</b>	4	1.5	1.5
<b>00843201</b>	5.5	1.5	1.5
<b>00840114</b>	6	1.5	1.5
<b>00840101</b>	8	1.5	1.5
<b>00840115</b>	8.5	1.5	1.5
<b>00840102</b>	10	1.5	1.5
<b>00840103</b>	11	1.5	1.5
<b>00840116</b>	12.5	1.5	1.5
<b>00840104</b>	15	1.5	1.5
<b>00840105</b>	17	1.5	1.5
<b>00840117</b>	17.5	1.5	1.5
<b>00840106</b>	25	1.5	1.5
<b>00840107</b>	35	2	2
<b>00843230</b>	45	2	2
<b>00840108</b>	50	2	2
<b>00843239</b>	60	2	2
<b>00840109</b>	70	2	2
<b>00840118</b>	85	2	2
<b>00840110</b>	90	2	2
<b>00840111</b>	110	2.5	2.5
<b>00840112</b>	125	2.5	2.5
<b>00840113</b>	175	2.5	4
<i>Setting master</i>			
<b>00843101</b>	225, 275	—	6

\* Making no allowance for a rim of 1 mm.

\*\* All listed values are determined through a 2-point measurement taken at half-height of the setting rina. The measuring direction is marked with 2 strokes. The measured actual dimension is engraved on every setting master.